







- 1) Lay one mat flat on the ground. Insert the connector's bolt up through the hole from under the mat. Keep the washer and bolt in your hand or aside to secure the mat to the connector from the top of the mat. Use the metal plate between the top of the mat and the washer if your site requires it as it may help keeping the pathway as flat & straight as possible.
- 2) Lay the second mat down on the side of the previous mat and slide it through the other side of the plastic connectors then secure them using the metal plate, washer and bolt. You now have two mats connected together with two single AccessLinks, 4' end-to-end, to form a track 16' long (you also can connect the mats side to side if you want a wider track, using the same procedure. In this case we recommend the use of three AccessLinks: two Accesslinks in each corner hole and one in the middle hole).
- 3) Repeat step two to make a track of unlimited length.

### **Installing a Double\*\* connector bolt**

Double plastic AccessLink is only used to connect four corners of mats together.

- 1) Lay two mats flat on the ground. Insert the connector's bolt up through the holes from under the mats corners. Keep the washer and bolt in your hand or aside to secure the mat to the connector from the top of the mat. Feel free to use the metal plate between the top of the mat and the washer if your site requires it.
- 2) Lay the third and fourth mats down on the side of the previous mats through the other side of the plastic connectors then secure them using the metal plate, washer and bolt. You now have four mats connected together with one double AccessLink, 8' end-to-end, to form a track 16' long.
- 3) Repeat step two to make a track of unlimited length.

### **Disassembling AccessDeck®**

To disassemble AccessDeck® with AccessLinks, simply tip the outermost sheet of AccessDeck® on its side, releasing the AccessLink, and slide the tipped sheet away from the adjacent sheet. Remove the AccessLink from the adjacent mat by tipping it sideways and sliding out. Repeat as necessary.

### **Transport, Storage and Maintenance**

AccessDeck® requires little maintenance and can be transported compactly. Its dimensions fit in the back of a pickup truck. Clean AccessDeck® sections using standard cleaning fluids and a hard bristle brush. Alternatively, a pressure washer may be used for deeper cleaning. Sections may be stacked on pallets (suggested 30 mats per pallet), banded and transported together using a forklift. AccessDeck® may be stored indoors or outdoors and may be stacked as high as can be safely accommodated.

AccessRec Team thanks you for choosing AccessDeck® for your portable roadway and other ground surface needs.